



XPRT-085

Thermal Receipt Printer 80mm

Key features:

- Support QR CODE Printing
- Support Chinese GB 18030
- 100MB Ethernet interface connection
- Avoid order missing
- Support black mark orientation
- Support oertype function
- Support 256K bytes NV logo download store and print



Specifications



Model	XPRT-085
Printing method	Direct thermal
Printing speed	260mm/s
Paper width	79.5±0.5mm
Paper diameter	80mm
Paper thickness	0.06~0.08mm
Column capacity	576 dots/line 512dots/line
Line space	3.75mm (changeable using commands)
Character size	ANK, Font A: 12×24 dots Font B: 9×17 dots Simplified/traditional Chinese: 24×24 dots
Bar code	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODABAR/ITF/CODE39/CODE93/CODE128 QR CODE
Code Page	PC347 (standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
NV FLASH	256K Bytes
Input buffer	2046K Bytes
Power supply	DC 24V/2.5A
Cash drawer control	DC 24V/1A
Interface	USB+Parallel/Serial+USB+LAN
Auto Cutter	Full/Partial(optional)
Reliability	Printing head life: 100 km Auto cutter life: 1 million cuts
Working environment	Temperature(0~45°C), humidity(10~80%)
Storage environment	Temperature(-10~60°C), humidity(10~90%)
Drivers	Win9X/Win ME/Win 2000/Win NT/Win XP/Win Vista/Win 7 /Win 8/Win 8.1/Linux/OPOS
Commend	Compatible with ESC/POS
Gross weight	1.52 kg
Dimension	200 × 140 × 140mm (D × W × H)