



POS58D

Thermal Receipt Printer

Key features:

- Cubic and fashionable design
- Dual mode Bluetooth & USB
- Front paper feed
- Error Reprinting Function



| Model | POS58D |
|---------------------|---|
| Printing method | Direct thermal |
| Printing speed | 100mm/s |
| Paper width | 48mm |
| Paper diameter | 60mm. |
| Paper thickness | 0.50~0.80mm |
| Paper Load | Top paper loading |
| Cutter | Partial cut |
| Sensor | Out-of-paper detection, Cover opening detection, over temperature detection, over voltage detection |
| Graphics | Bitmap printing standard |
| Barcode Type | 1D: UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 2D: QR CODE, PDF417 |
| Memory | RAM 2 MB. ROM 4 MB. |
| Font | Simplified Chinese/Traditional Chinese/Korean/Japanese, 47 codepages |
| Power supply | Input: AC 100-240V, 50/60Hz / Output: DC 12V/2A |
| LED Indicator | Front LED indicator |
| Interface | USB + Bluetooth, 24V.Cash Drawer |
| Auto Cutter | Partial cut or Full cut |
| Reliability | Printing head life: 50 km Auto cutter life: 1 million cuts |
| Working environment | Temperature(0~40°C), humidity (20~85%) |
| Storage environment | Temperature(-20~60°C), humidity (5~95%) |
| Drivers | Windows, Linux, Android |
| Commend | Compatible with ESC/POS |
| Dimension | 110 x 106 x 114mm. (L)x(W)x(H) |

